* Fleming



UK&NI: +44 (0) 2871 342637

ROI: 048 71 342637

info@fleming-agri.com

Muck Spreaders





- 30-50HP requirement
- 1 yd³ capacity (0.85m³)
- PTO speed 540 rpm
- o 3/8" (10mm) discharge chains
- Easy access loading height 600mm
- A five stage paint & heat treatment process for better corrosion protection and durability



Specification

Model	MINIMUCK	
Cubic yard capacity	1	
Power required	30hp	
Door	N/A	
Chain/Flails	10no x 10mm	
Drum thickness	3mm	
Overall length	1.5m	
Width	1m	
Loading height	60cm	
Lights	N/A	
Brakes	N/A	
Unladen	200kg	
PTO Speed	540rpm	
Diameter of drum	90cm	
Length of drum	125cm	
Wheel sizes standard	N/A	
Wheel sizes optional	N/A	

· : +44 (0) 2871 342637





- 25-50HP compact tractor requirement.
- 2.25yd³ capacity (1.7m³)
- PTO speed 540 rpm
- Heavy duty 10mm hardened steel chain flails to give efficient unloading time
- 10mm (3/8") discharge chains
- 1m loading height





Specification

Model	MS150	
Cubic yard capacity	2.25	
Power required	30hp	
Door	N/A	
Chain/Flails	14no x 10mm	
Drum thickness	3mm	
Overall length	3m	
Width	1.4m	
Loading height	1m	
Lights	N/A	
Brakes	N/A	
Unladen	500kg	
PTO Speed	540rpm	
Diameter of drum	1.05m	
Length of drum	1.83m	
Wheel sizes standard	10x80x12	
Wheel sizes optional	N/A	

: +44 (0) 2871 342637





- 35-80HP requirement
- 4 yd³ capacity (3m³)
- Heavy duty 4 bolt flange bearings mounted away from the body for low maintenance
- A five stage paint & heat treatment process for better corrosion protection and durability
- Starter bars for quick start up
- PTO speed 540 rpm
- Pick up eye and shoe and PTO rest as standard
- Heavy duty 25mm (1") simplex drive chain
- Reinforced loading edge



Specification

Model	MS450	
Cubic yard capacity	4	
Power required	40hp	
Door	Manual	
Chain/Flails	20no x 10mm	
Drum thickness	3mm	
Overall length	4.07m	
Width	1.84m	
Loading height	1.2m	
Lights	N/A	
Brakes	N/A	
Unladen	950kg	
PTO Speed	540rpm	
Diameter of drum	120cm	
Length of drum	250cm	
Wheel sizes standard	11.5x80x15.3	
Wheel sizes optional	12.5x80x15.3	

: +44 (0) 2871 342637





- 6.5yd³capacity (5m³)
- 60 100HP requirement
- Heavy duty 4 bolt flange bearings mounted away from the body for low maintenance
- PTO speed 540 rpm
- Heavy duty 30mm (1 1/4") simplex drive chain
- 6 ton 6 stud 70mm square bolt on axle for safe working operation with 385 x 65R x 22.5 as standard wheels
- Double starter bars for quick start up









Specification

- p		
Model	MS700	
Cubic yard capacity	6.5	
Power required	60hp	
Door	HYD	
Chain/Flails	28no x 13mm	
Drum thickness	4mm	
Overall length	4.7m	
Width	2.1m	
Loading height	1.48m	
Lights	Standard	
Brakes	Standard	
Unladen	1500kg	
PTO Speed	540rpm	
Diameter of drum	140cm	
Length of drum	3m	
Wheel sizes standard	385x65rx22.5	
Wheel sizes optional	12.5x80x15.3 550x45x22.5	

\(: +44 (0) 2871 342637





- 9.5yd³ capacity (7.25m³)
- 100 Hp minimum requirement
- 45mm (3/4") input shaft
- Heavy duty 4 bolt flange bearings mounted away from the body for low maintenance
- PTO speed 540 rpm
- Double starter bars for quick start up
- Heavy duty 25mm (1") duplex drive chain
- Large wash-out bung



Specification

Model	MS1000	
Cubic yard capacity	9.5	
Power required	100hp	
Door	HYD	
Chain/Flails	36no x 13mm	
Drum thickness	4mm	
Overall length	5.6m	
Width	2.5m	
Loading height	1.67m	
Lights	Standard	
Brakes	Standard	
Unladen	1800kg	
PTO Speed	540rpm	
Diameter of drum	150cm	
Length of drum	370cm	
Wheel sizes standard	550x60x22.5	
Wheel sizes optional	POA	

\(: +44 (0) 2871 342637

* Fleming

Muck Spreaders

Muck Forks

- 5ft model (SGMF5) has 8 tines in base and 2 optional side tines
- 6ft model (SGMF6) has 9 tines in base and 2 optional side tines
- Ideal for muck and silage
- Heavy duty structural box section frame with bushed main beam
- Suitable for tractor mounted front end loaders



Specification

<u> </u>				
Model	SGMF5	SGMF6		
Width (m)	1.5	1.82		
Height (m)	1	1		
Tines	10	11		
Weight	153kg	172kg		





General Purpose Grab

- 4ft model (SGB4) has 6 tines in base & 2 optional side tines for secure capacity
- 5ft model (SGB5) has 8 tines in base & 2 optional side tines
- 6ft model (SGB6) has 9 tines in base & 2 optional side tines
- Curved tines are seated in pinched sockets to prevent tine turning during operation
- 890mm opening for large payload
- All hinge points fitted with grease points
- 2 heavy duty hydraulic cylinders for good gripping action and low power requirement
- Locked pivot pins to prevent excessive wear with easy access grease points
- Good ram clearance for smooth operation
- Heavy duty structural box section frame with bushed main beam







Model	SGB4	SGB5	SGB6
Width (m)	1.25	1.52	1.84
Tines	12	15	17
Hyd Rams	2	2	2
Capacity (m³)	0.5	0.7	0.9
Weight	218kg	240kg	310kg

: +44 (0) 2871 342637



*Fleming



Fleming Agri Products has over 160 years of manufacturing experience spanning over 5 generations of the Fleming family.

The company is now one of the leading manufacturers of agricultural equipment with a dealer network that covers not only the British Isles & Ireland, but also Europe, USA, Australia and New Zealand.

MEET OUR SALES TEAM



David Meban Sales Manager (Sales South West Eng & Wales) Tel: +44 (0) 7794018020 davidmeban@fleming-agri.com



David Watters
(Sales Scot & N.Eng)
Tel: +44 (0) 7944682304
davidwatters@fleming-agri.com



Adrian Brown
(Sales Central & South East England)
Tel: +44 (0) 7778128054
adrianbrown@fleming-agri.com



Bryan Hunter
(Sales Ireland)

NI Tel: +44 (0) 7967721606

Rep of Ire Tel: 01 5267419
bryan@fleming-agri.com



Gareth Walker
(Office/Export Sales)
Tel: +44 (0) 7557782872
gareth@fleming-agri.com



Alison Duncan (Marketing/Office Sales) Tel: +44 (0) 7778128055 alison@fleming-agri.com

Contact sales executives on mobile numbers

Newbuildings Industrial Estate, Newbuildings, Northern Ireland, BT47 2SX

